

MODEL: ATL-1315Bi

Handheld OTDR



Key points

- Multiple wavelengths ((1310, 1550nm) support LAN, datacenters, PON, FTTx and outside plant applications as well as customized wavelengths.
- 800×480, 7-inch TFT color LCD touch screen places power and convenience at your finger steps
- Minimum 2.5cm resolution which enables it to locate the event point accurately
- Event dead zone of 0.5m which makes the near connection easy to be supervised
- Automatic monitoring and alarm of incoming optical signals
- Bi-directional Analysis to minimize the possible mismatches
- A maximum dynamic range of 46dB, and 256k data sampling points
- Penetrate an optical splitter of up to 1:128



Technical Specifications

OTDR Module	Wavelength \pm 20nm	Dynamic Range (dB)	EDZ(m)	ADZ(m)
ATL-1315Bi	1310/1550nm	37/35	0.5	3
Distance Accuracy	$\pm(0.75 + \text{sample interval} + 0.0025\% \times \text{range})$ (excluding the refractivity placement error) (m)			
Ranging resolution	0.05, 0.1, 0.2, 0.5, 1, 2, 4, 8, 16 and 32m			
Test range	0.4, 0.8, 1.6, 3.2, 6.4, 16, 32, 64, 128, 256 and 512km (single-mode);			
Pulse Width	3, 5, 10, 30, 80, 160, 320, 640, 1280, 5120, 10240 and 20480ns			
Sampling Point	256k			
Linearity	0.03 dB / dB			
Loss Resolution	0.001 dB			
Reflectance Accuracy	± 2 dB			
Refractive Index	1.00000 ~ 1.99999(step: 0.00001)			
Storage	200000 traces with 32GB SD card			
Display	800×480, 7-inch TFT color LCD (a capacitive touch screen in the standard configuration, and a resistive touch screen optional)			
Optical Output Interface	FC/UPC (standard configuration, with SC/UPC, SC/APC and FC/APC (Optional)			
Power Supply	AC/DC adapter: AC100V~240V, 50/60Hz and 1.5A DC: 17V \pm 3V(2A) Internal Li battery: 10.8V, 6400mAh, battery operating time: 12h			
External interfaces	USB, Micro-USB, 10M/100M Ethernet, earphone and Micro SD			
Dimensions	252mm(W)×180mm (H)×55mm (D)			
Weight	About 1.5kg			
Environmental adaptability	Operating temperature: -10°C~+60°C Storage temperature: -20°C ~+70°C RH: 5% ~95%, no condensation			
Accessories	AC/DC charger, Carry Case			

Registered Office: TF-7, 3rd floor, Empire square building, Jawahar Colony, Road No.36, jubilee Hills, Hyderabad Telangana.
email: support@telogica.com Website: www.telogica.com