

OPTICAL LASER SOURCE

Model: DLSDT-01



Features:

- ✓ **DLSDT-01** is an advanced version of Laser Sources, with better features and more functions.
- ✓ Offers excellent stability and portability for accurate fiber testing.
- ✓ Single output port provides stable laser power at dual wave lengths.
- ✓ High stability of the output power
- ✓ The compact unit operates in either continuous wave (CW) mode or Modulated mode.
- ✓ Easy-to –use, Straight forward Operation.
- ✓ Eye- catching handheld appearance.
- ✓ LCD backlight for easy operation in dark environment.
- ✓ Recommended calibration interval.

Specifications:

Model	DLSDT-01
Laser Type	FP-LD
Fiber Type	SM 10/125 and SM9/125
Optical Connectors	FC/PC (Interchangeable FC/SC/ST connectors can be optional)
Stability	±0.03dB/15min; ±0.1dB/8hrs
Laser Modulation	CW,270Hz, 1Khz, 2Khz
Resolution	0.01dB
Output power	>-7dBm @1310nm/1550nm
Display	LCD with backlight
Size	175*90*45
Weight	255g
Power Supply	Rechargeable Battery (3 AA 1.5V batteries)
Battery Operating Time(hour)	45(without backlight)
Operating Environments	Temperature; -10 to +60 Deg C Humidity; RH95% or less non-condensing
Storage Environments	Temperature; -20 to +70 Deg C Humidity; RH95% or less non condensing
Accessories	3*AA rechargeable batteries, Carrying bag, user manual.